

Ubuntu Server 18.04 LTS

ddclient with No-IP

```
sudo apt install ddclient
```

[/etc/ddclient.conf](#)

```
# Configuration file for ddclient generated by debconf
#
# /etc/ddclient.conf

protocol=noip
use=web
web=checkip.dyndns.org
server=dynupdate.no-ip.com
login=XX No-IP login email XX
password=XX No-IP login password XX
XX No-IP Hostname XX
```

Einstellung testen:

```
ddclient -daemon=0 -debug -verbose -noquiet
```

[/etc/default/ddclient](#)

```
# Configuration for ddclient scripts
# generated from debconf on Sun Mar 10 17:54:08 CET 2019
#
# /etc/default/ddclient

# Set to "true" if ddclient should be run every time DHCP client
('dhclient'
# from package isc-dhcp-client) updates the systems IP address.
run_dhclient="false"

# Set to "true" if ddclient should be run every time a new ppp
connection is
# established. This might be useful, if you are using dial-on-demand.
run_ipup="false"

# Set to "true" if ddclient should run in daemon mode
# If this is changed to true, run_ipup and run_dhclient must be set to
false.
run_daemon="true"
```

```
# Set the time interval between the updates of the dynamic DNS name in  
seconds.  
# This option only takes effect if the ddclient runs in daemon mode.  
daemon_interval="3600"
```

```
sudo service ddclient restart
```

From:
<http://www.andreasgiemza.de/> - Andreas' Wiki

Permanent link:
http://www.andreasgiemza.de/software_handreichungen/ubuntu_server_18.04_lts?rev=1552245542

Last update: 2019/03/10 20:19

